

Description

Fastener Length: 5/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3243-5-09](#)

SKU / Model:	CR324359
Minimum Qty (MOQ):	100
NSN:	5320-01-092-8759
Schedule B:	7318.16.0060
ECCN:	EAR99



* See page 2 for technical characteristics

P/N CR3243-5-9 Specifications

Fastener Length:	0.674 Inches Minimum And 0.694 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.302 Inches Minimum And 0.324 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams6322 Assn Std 2nd Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec 1st Material Response Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416 Type2,class 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3243-5-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.