

**Description**

diameter: 3/16", grip range: 0.063" - 0.125", universal head, locked spindle, oversized diameter, 5056 aluminum sleeve, 8740 steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR3243-6-2](#)

SKU / Model:	CR3243602
Minimum Qty (MOQ):	100
NSN:	5320-01-033-9125
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



## P/N CR3243-6-02 Specifications

<b>Fastener Length:</b>	0.255 Inches Minimum And 0.275 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.202 Inches Minimum And 0.205 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>End Item Identification:</b>	Aircraft, B-2 Bomber (atb); Aircraft, Phantom F-4; Aircraft, Stratofortress B-52; Engine, Aircraft, Tf-33-p-7 (c-141a/b); Aircraft, Stratolifter C-135; Aircraft, Delta Dart F-106; Helicopter, Iroquois Uh-1; Aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130); U-2 Support Equipment; Aircraft, Hercules C-130
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Special Features:</b>	Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
<b>Material:</b>	Aluminum Alloy 5056 Body
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Ams 6322 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Body
<b>Surface Treatment:</b>	Chromate Body
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Body
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3243-6-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.