

## P/N CR3243-6-11

## **Description**

diameter: 3/16", grip range: 0.625" - 0.687", universal head, locked spindle, oversized diameter, 5056 aluminum sleeve, 8740 steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: CR3243611

Minimum Qty (MOQ): 100

NSN: 5320-01-353-7949

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# P/N CR3243-6-11 Specifications

Fastener Length:	2.090 Inches Minimum And 2.100 Inches Maximum
Grip Length:	0.626 Inches Minimum And 0.687 Inches Maximum
Material:	Iron Alloy 660 Locking Ringaluminum Alloy 5056 Sleevesteel Comp 8740 Stem

### **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/CR3243-6-11">https://military-fasteners.com/rivets/blind+rivets/CR3243-6-11</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR3243-6-11">https://military-fasteners.com/rivets/blind+rivets/CR3243-6-11</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR3243-6-11">https://military-fasteners.com/rivets/blind+rivets/CR3243-6-11</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR3243-6-11">https://military-fasteners.com/rivets/blind+rivets/CR3243-6-11</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/cR3243-6-11">https://military-fasteners.com/rivets/blind+rivets/cR3243-6-11</a> and selecting the quantity you want then cart in the properties of the properti