

P/N CR3243-6-12

Description

diameter: 3/16", grip range: 0.688" - 0.750", universal head - locked spindle - oversized diameter - 5056 aluminum sleeve - 8740 steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR3243612
Minimum Qty (MOQ):	100
NSN:	5320-01-353-7948
ECCN:	EAR99



^{*} See page 2 for technical characteristics

P/N CR3243-6-12 Specifications

Fastener Length:	2.160 Inches Minimum And 2.170 Inches Maximum
Grip Length:	0.688 Inches Minimum And 0.750 Inches Maximum
Material:	Iron Alloy 660 Locking Ringaluminum Alloy 5056 Sleevesteel Comp 8740 Stem

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3243-6-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3243-6-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3243-6-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3243-6-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/cR3243-6-12 and selecting the quantity you want then cart in the properties of the properti