

P/N CR3243-6-3

Military-Fasteners.com

Description

diameter: 3/16", grip range: 0.126" - 0.187", universal head, locked spindle, oversized diameter, aluminum sleeve, steel stem, CR3243 series rivet

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

<u>CR3243-6-03</u>	
SKU / Model:	CR324363
Minimum Qty (MOQ):	100
NSN:	5320-01-033-8638
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N CR3243-6-3 Specifications

0.318 Inches Minimum And 0.338 Inches Maximum
Universal
0.080 Inches Minimum And 0.090 Inches Maximum
0.202 Inches Minimum And 0.205 Inches Maximum
Self-plugging Mechanically Locked Stem
0.356 Inches Minimum And 0.394 Inches Maximum
Serrated Stem-type W
0.126 Inches Minimum And 0.187 Inches Maximum
Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Aluminum Alloy 5056 Body
Steel Comp 8740 Stem
Ams 6322 Assn Std Single Material Response Stem
Qq-a-430 Fed Spec Single Material Response Body
Chromate Body
Cadmium Stem
Mil-c-5541 Mil Spec Single Treatment Response Body
Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/CR3243-6-3</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.