



Military-Fasteners.com

P/N CR3245-4-03

Description

diameter: 1/8", grip range: 0.126"-0.187", unisink head, locked spindle, oversized diameter, aluminum sleeve, steel stem, CR3245 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3245-4-3](#)

SKU / Model:	CR3245403
Minimum Qty (MOQ):	100
NSN:	5320-01-165-1386
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N CR3245-4-03 Specifications

Fastener Length:	0.266 Inches Minimum And 0.286 Inches Maximum
Head Style:	Oval Countersunk
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.230 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3245-4-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.