

**Description**

diameter: 1/8", grip range: 0.188" - 0.250", unisink head, locked spindle, oversized diameter, 5056 aluminum sleeve, 8740 steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	CR3245404
Minimum Qty (MOQ):	100
NSN:	5320-01-165-1387
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



## P/N CR3245-4-04 Specifications

<b>Fastener Length:</b>	0.328 Inches Minimum And 0.348 Inches Maximum
<b>Head Style:</b>	Oval Countersunk
<b>Shank Diameter:</b>	0.139 Inches Minimum And 0.143 Inches Maximum
<b>Head Major Diameter:</b>	0.230 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Ams 6322 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Surface Treatment:</b>	Chromate Sleeve
<b>Surface Treatment:</b>	Cadmium Stem And Chromate Stem
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3245-4-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.