

**Description**

diameter: 1/8", grip range: 0.251" - 0.312", unisink head, locked spindle, oversized diameter, 5056 aluminum sleeve, 8740 steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR3245-4-5](#)

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | CR3245405           |
| Minimum Qty (MOQ):      | 100                 |
| NSN:                    | 5320-01-165-1388    |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



## P/N CR3245-4-05 Specifications

|   |   |
|---|---|
| <b>Fastener Length:</b>                               | 0.391 Inches Minimum And 0.411 Inches Maximum                   |
| <b>Head Style:</b>                                    | Oval Countersunk  |
| <b>Shank Diameter:</b>                                | 0.139 Inches Minimum And 0.143 Inches Maximum                   |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem                          |
| <b>Head Major Diameter:</b>                           | 0.230 Inches Maximum  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W  |
| <b>Grip Length:</b>                                   | 0.251 Inches Minimum And 0.312 Inches Maximum                   |
| <b>Countersink Angle:</b>                             | 98.5 Degrees Minimum And 101.5 Degrees Maximum                  |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve                                      |
| <b>Material:</b>                                      | Steel Comp 8740 Stem  |
| <b>Material Document And Classification:</b>          | Ams 6322 Assn Std Single Material Response Stem                 |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve               |
| <b>Surface Treatment:</b>                             | Chromate Sleeve   |
| <b>Surface Treatment:</b>                             | Cadmium Stem And Chromate Stem                                  |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-5541 Mil Spec Single Treatment Response Sleeve            |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Stem |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3245-4-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.