

**Description**

Fastener Length: 3/8", CR3245 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR3245-4-05](#)

SKU / Model:	CR324545
Minimum Qty (MOQ):	100
NSN:	5320-01-165-1388
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N CR3245-4-5 Specifications

<b>Fastener Length:</b>	0.391 Inches Minimum And 0.411 Inches Maximum
<b>Head Style:</b>	Oval Countersunk
<b>Shank Diameter:</b>	0.139 Inches Minimum And 0.143 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.230 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.251 Inches Minimum And 0.312 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Ams 6322 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Surface Treatment:</b>	Chromate Sleeve
<b>Surface Treatment:</b>	Cadmium Stem And Chromate Stem
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3245-4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.