

Description

diameter: 5/32", grip range: 0.126" - 0.187", locked spindle, oversized diameter, aluminum sleeve, steel stem, CR3245 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR324553
Minimum Qty (MOQ):	100
NSN:	5320-01-229-4120
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N CR3245-5-3 Specifications

Head Style:	Shovel
Head Height:	0.030 Inches Minimum And 0.040 Inches Maximum
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Maximum
Countersink Height:	0.015 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Special Features:	100.0 Deg Countersunk Head
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Surface Treatment:	Chromate Sleeve
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3245-5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.