



Military-Fasteners.com

P/N CR3245-5-3

Description

diameter: 5/32", grip range: 0.126" - 0.187", locked spindle, oversized diameter, aluminum sleeve, steel stem, CR3245 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | CR324553            |
| Minimum Qty (MOQ):      | 100                 |
| NSN:                    | 5320-01-229-4120    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics



# P/N CR3245-5-3 Specifications

|  |  |
|--|--|
| Head Style:                                    | Shovel   |
| Head Height:                                   | 0.030 Inches Minimum And 0.040 Inches Maximum              |
| Shank Diameter:                                | 0.172 Inches Minimum And 0.176 Inches Maximum              |
| Shank Style:                                   | Self-plugging Mechanically Locked Stem                     |
| Head Major Diameter:                           | 0.296 Inches Maximum                                       |
| Countersink Height:                            | 0.015 Inches Nominal                                       |
| Expansion Device:                              | Serrated Stem-type W                                       |
| Grip Length:                                   | 0.126 Inches Minimum And 0.187 Inches Maximum              |
| Special Features:                              | 100.0 Deg Countersunk Head                                 |
| Material:                                      | Aluminum Alloy 5056 Sleeve                                 |
| Material:                                      | Steel Comp 8740 Stem                                       |
| Material Document And Classification:          | Qq-a-430 Fed Spec Single Material Response Sleeve          |
| Material Document And Classification:          | Ams 6322 Assn Std Single Material Response Stem            |
| Surface Treatment:                             | Chromate Sleeve  |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Sleeve       |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Stem |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3245-5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.