

Description

diameter: 5/32", grip range: 0.126" - 0.187", locked spindle, oversized diameter, aluminum sleeve, steel stem, CR3245 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | CR324553 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-229-4120 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N CR3245-5-3 Specifications

| | |
|---|--|
| Head Style: | Shovel |
| Head Height: | 0.030 Inches Minimum And 0.040 Inches Maximum |
| Shank Diameter: | 0.172 Inches Minimum And 0.176 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.296 Inches Maximum |
| Countersink Height: | 0.015 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.126 Inches Minimum And 0.187 Inches Maximum |
| Special Features: | 100.0 Deg Countersunk Head |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Comp 8740 Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Material Document And Classification: | Ams 6322 Assn Std Single Material Response Stem |
| Surface Treatment: | Chromate Sleeve |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3245-5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.