

**Description**

CR3245-5-4 Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3245-5-04](#)

SKU / Model:	CR324554
Minimum Qty (MOQ):	100
NSN:	5320-01-229-4121
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3245-5-4 Specifications

<b>Head Style:</b>	Shovel
<b>Head Height:</b>	0.030 Inches Minimum And 0.040 Inches Maximum
<b>Shank Diameter:</b>	0.172 Inches Minimum And 0.176 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.296 Inches Maximum
<b>Countersink Height:</b>	0.015 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Special Features:</b>	100.0 Deg Countersunk Head
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Material Document And Classification:</b>	Ams 6322 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Chromate Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3245-5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.