

Description

diameter: 3/16", grip range: 0.313" - 0.375", unisink head - locked spindle - oversized diameter - 5056 aluminum sleeve - 8740 steel stem


* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3245-6-6](#)

SKU / Model:	CR3245606
Minimum Qty (MOQ):	100
NSN:	5320-01-230-3468
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N CR3245-6-06 Specifications

Head Style:	Shovel
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.200 Inches Minimum And 0.204 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.363 Inches Maximum
Countersink Height:	0.023 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Special Features:	100.0 Deg Countersunk Head
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Surface Treatment:	Chromate Sleeve
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3245-6-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.