

Description

diameter: 1/8", grip range: 0.063" - 0.125", flush head, oversized diameter, aluminum sleeve, steel stem, CR3246 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR3246402
Minimum Qty (MOQ):	100
NSN:	5320-01-337-7876
Schedule B:	7318.23.0000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N CR3246-4-02 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.125 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Corrosion Resisting Locking Ringaluminum Alloy 5056 Sleeve Steel Stem
Surface Treatment:	Chromate Sleeve Cadmium Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3246-4-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.