

P/N CR3246-4-02

Description

diameter: 1/8", grip range: 0.063" - 0.125", flush head, oversized diameter, aluminum sleeve, steel stem, CR3246 series rivet

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: CR3246402

Minimum Qty (MOQ): 100

NSN: 5320-01-337-7876

Schedule B: 7318.23.0000

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N CR3246-4-02 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.125 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Corrosion Resisting Locking Ringaluminum Alloy 5056 Sleevesteel Stem
Surface Treatment:	Chromate Sleevecadmium Stem

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3246-4-02 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3246-4-02 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3246-4-02 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3246-4-02 and selecting the quantity you want then click "add to cart".