

# P/N CR3246-4-3

### **Description**

Blind Rivet part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	CR324643
Minimum Qty (MOQ):	100
NSN:	5320-01-337-7877
ECCN:	EAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N CR3246-4-3 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.125 Inches Minimum And 0.187 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Corrosion Resisting Locking Ringaluminum Alloy 5056 Sleevesteel Stem
Surface Treatment:	Chromate Sleevecadmium Stem

### **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/CR3246-4-3">https://military-fasteners.com/rivets/blind+rivets/CR3246-4-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR3246-4-3">https://military-fasteners.com/rivets/blind+rivets/CR3246-4-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR3246-4-3">https://military-fasteners.com/rivets/blind+rivets/CR3246-4-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR3246-4-3">https://military-fasteners.com/rivets/blind+rivets/CR3246-4-3</a> and selecting the quantity you want then