

**Description**

diameter: 5/32", grip range: 0.063" - 0.125", flush head, oversized diameter, 5056 aluminum sleeve - steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	CR3246502
Minimum Qty (MOQ):	100
NSN:	5320-01-337-7880
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N CR3246-5-02 Specifications

<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Head Major Diameter:</b>	0.282 Inches Minimum And 0.290 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.125 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Corrosion Resisting Locking Ringaluminum Alloy 5056 Sleeve Steel Stem
<b>Surface Treatment:</b>	Chromate Sleeve Cadmium Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3246-5-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.