

**Description**

diameter: 1/8", grip range: 0.063" - 0.125", 100°, flush head - oversized diameter - 5056 aluminum sleeve - 15-7 ph corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	CR3252402
Minimum Qty (MOQ):	100
NSN:	5320-01-628-5215

NO IMAGE  
AVAILABLE

## P/N CR3252-4-02 Specifications

<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Head Major Diameter:</b>	0.125 Inches Nominal
<b>Special Features:</b>	100 Degree Flush Head,manufacturer Identification,lock Collar Finish Passivated
<b>Material:</b>	Aluminum Alloy Sleeve
<b>Material:</b>	Steel Corrosion Resisting Stem
<b>Material:</b>	Steel Corrosion Resisting Collar
<b>Material Document And Classification:</b>	Mil-c-544 Mil Spec 2nd Material Response Sleeve
<b>Material Document And Classification:</b>	Ams5657 National Std/spec 1st Material Response Stem
<b>Material Document And Classification:</b>	Ams5731 National Std/spec 3rd Material Response Collar
<b>Surface Treatment:</b>	Oxide Film Sleeve
<b>Surface Treatment:</b>	Cadmium Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3252-4-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.