

Description

diameter: 1/8", grip range: 0.063" - 0.125", 100°, flush head - oversized diameter - 5056 aluminum sleeve - 15-7 ph corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR3252402
Minimum Qty (MOQ):	100
NSN:	5320-01-628-5215



P/N CR3252-4-02 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Head Major Diameter:	0.125 Inches Nominal
Special Features:	100 Degree Flush Head,manufacturer Identification,lock Collar Finish Passivated
Material:	Aluminum Alloy Sleeve
Material:	Steel Corrosion Resisting Stem
Material:	Steel Corrosion Resisting Collar
Material Document And Classification:	Mil-c-544 Mil Spec 2nd Material Response Sleeve
Material Document And Classification:	Ams5657 National Std/spec 1st Material Response Stem
Material Document And Classification:	Ams5731 National Std/spec 3rd Material Response Collar
Surface Treatment:	Oxide Film Sleeve
Surface Treatment:	Cadmium Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3252-4-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.