

Description

diameter: 1/8", grip range: 0.063" - 0.125", 100°, flush head - oversized diameter - 5056 aluminum sleeve - 15-7 ph corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | CR3252402 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-628-5215 |

NO IMAGE
AVAILABLE

P/N CR3252-4-02 Specifications

| | |
|--|---|
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Head Major Diameter: | 0.125 Inches Nominal |
| Special Features: | 100 Degree Flush Head,manufacturer Identification,lock Collar Finish Passivated |
| Material: | Aluminum Alloy Sleeve |
| Material: | Steel Corrosion Resisting Stem |
| Material: | Steel Corrosion Resisting Collar |
| Material Document And Classification: | Mil-c-544 Mil Spec 2nd Material Response Sleeve |
| Material Document And Classification: | Ams5657 National Std/spec 1st Material Response Stem |
| Material Document And Classification: | Ams5731 National Std/spec 3rd Material Response Collar |
| Surface Treatment: | Oxide Film Sleeve |
| Surface Treatment: | Cadmium Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3252-4-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.