

**Description**

diameter: 1/8", grip range: 0.126" - 0.187", flush head, oversized diameter, aluminum sleeve, corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR3252-4-3](#)

|                         |                                             |
|-------------------------|---------------------------------------------|
| SKU / Model:            | CR3252403                                   |
| Minimum Qty (MOQ):      | 100                                         |
| NSN:                    | 5320-01-148-2364                            |
| Schedule B:             | 7616.10.3000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N CR3252-4-03 Specifications

|                                                       |                                                                                |
|-------------------------------------------------------|--------------------------------------------------------------------------------|
| <b>Fastener Length:</b>                               | 0.291 Inches Minimum And 0.311 Inches Maximum                                  |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                                | 0.139 Inches Minimum And 0.143 Inches Maximum                                  |
| <b>Head Major Diameter:</b>                           | 0.221 Inches Minimum And 0.229 Inches Maximum                                  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W                                                           |
| <b>Grip Length:</b>                                   | 0.126 Inches Minimum And 0.187 Inches Maximum                                  |
| <b>Minimum Tensile Strength:</b>                      | 345 Pounds Per Square Inch                                                     |
| <b>Shear Strength:</b>                                | 614 Single Pounds Per Square Inch                                              |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                 |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve                                                     |
| <b>Material:</b>                                      | Iron Alloy 660 Locking Ring                                                    |
| <b>Material:</b>                                      | Steel Comp 632 Stem                                                            |
| <b>Material Document And Classification:</b>          | Ams 5657 Assn Std Single Material Response Stem                                |
| <b>Material Document And Classification:</b>          | Ams 5731 Fed Spec Single Material Response Locking Ring                        |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve                              |
| <b>Surface Treatment:</b>                             | Chromate Sleeve                                                                |
| <b>Surface Treatment:</b>                             | Cadmium Stem                                                                   |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-5541 Mil Spec Single Treatment Response Sleeve                           |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 1,class 2 Fed Spec Single Treatment Response Stem                |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3252-4-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.