

Description

diameter: 1/8", grip range: 0.313" - 0.375", 100°, flush head - oversized diameter - 5056 aluminum sleeve - 15-7 ph corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR3252406
Minimum Qty (MOQ):	100
NSN:	5320-00-006-8513
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N CR3252-4-06 Specifications

Fastener Length:	0.531 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Nickel Alloy 600 Stem
Material Document And Classification:	Ams 5665 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Specification/standard Data:	80205-nas1739 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3252-4-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.