

Description

diameter: 3/16", grip range: 0.126" - 0.187", 100°, flush head - oversized diameter - 5056 aluminum sleeve - 15-7 ph corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR3252603
Minimum Qty (MOQ):	100
NSN:	5320-01-521-4293
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



P/N CR3252-6-03 Specifications

Fastener Length:	0.328 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.115 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Iron Alloy Locking Ring Or Steel Locking Ring
Surface Treatment:	Anodize Sleeve
Surface Treatment:	Passivate Grip
Surface Treatment:	Passivate Locking Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Grip
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3252-6-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.