

Description

Cr Max Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | CR325263 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5320-01-521-4293 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3252-6-3 Specifications

| | |
|-------------------------------------------------------|--------------------------------------------------------------------------------|
| Fastener Length: | 0.328 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.115 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.349 Inches Minimum And 0.357 Inches Maximum |
| Grip Length: | 0.126 Inches Minimum And 0.187 Inches Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Iron Alloy Locking Ring Or Steel Locking Ring |
| Surface Treatment: | Anodize Sleeve |
| Surface Treatment: | Passivate Grip |
| Surface Treatment: | Passivate Locking Ring |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Grip |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Locking Ring |

How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3252-6-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.