

**Description**

Fastener Length: 15/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR325269
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-150-2768
Schedule B:	7616.10.3000
ECCN:	EAR99

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in all caps.

NO IMAGE  
AVAILABLE

## P/N CR3252-6-9 Specifications

<b>Fastener Length:</b>	0.950 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.201 Inches Nominal
<b>Shank Style:</b>	Self-plugging High Clinch Shank
<b>Head Major Diameter:</b>	0.353 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.501 Inches Minimum And 0.562 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Corrosion Resisting Locking Ring
<b>Material:</b>	Steel Corrosion Resisting Stem
<b>Material Document And Classification:</b>	Ams5657 Assn Std 3rd Material Response Stem
<b>Material Document And Classification:</b>	Ams5731 Assn Std 1st Material Response Locking Ring
<b>Material Document And Classification:</b>	Qq-c-430 Fed Spec 2nd Material Response Sleeve

## How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3252-6-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.