

Description

diameter: 1/8", grip range: 0.025" - 0.062", universal head, oversized diameter, 5056 aluminum sleeve, 15-7 ph corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3253-4-1](#)

SKU / Model:	CR3253401
Minimum Qty (MOQ):	100
NSN:	5320-01-150-5954
ECCN:	EAR99

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3253-4-01 Specifications

Fastener Length:	0.370 Inches Nominal
Head Style:	Universal
Head Height:	0.054 Inches Nominal
Shank Diameter:	0.140 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.250 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.025 Inches Minimum And 0.062 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Corrosion Resisting Locking Ring
Material:	Steel Corrosion Resisting Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-4-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.