

## Description

diameter: 1/8", grip range: 0.025" - 0.062", universal head, oversized diameter, 5056 aluminum sleeve, 15-7 ph corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[CR3253-4-1](#)

SKU / Model:	CR3253401
Minimum Qty (MOQ):	100
NSN:	5320-01-150-5954
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N CR3253-4-01 Specifications

<b>Fastener Length:</b>	0.370 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Nominal
<b>Shank Diameter:</b>	0.140 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.250 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.025 Inches Minimum And 0.062 Inches Maximum
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Corrosion Resisting Locking Ring
<b>Material:</b>	Steel Corrosion Resisting Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-4-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.