

**Description**

diameter: 1/8", grip range: 0.126" - 0.187", universal head, oversized diameter, aluminum sleeve, corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3253-04-03](#) [CR3253-4-3](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | CR3253403                                   |
| Minimum Qty (MOQ):      | 100   |
| NSN:                    | 5320-01-156-0252                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

## P/N CR3253-4-03 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.291 Inches Minimum And 0.311 Inches Maximum              |
| <b>Head Style:</b>                                    | Universal  |
| <b>Head Height:</b>                                   | 0.054 Inches Minimum And 0.064 Inches Maximum              |
| <b>Shank Diameter:</b>                                | 0.139 Inches Minimum And 0.143 Inches Maximum              |
| <b>Head Major Diameter:</b>                           | 0.240 Inches Minimum And 0.260 Inches Maximum              |
| <b>Expansion Device:</b>                              | Serrated Stem-type W                                       |
| <b>Grip Length:</b>                                   | 0.126 Inches Minimum And 0.187 Inches Maximum              |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve                                 |
| <b>Material:</b>                                      | Iron Alloy 660 Locking Ring                                |
| <b>Material:</b>                                      | Steel Comp 632 Stem  |
| <b>Material Document And Classification:</b>          | Ams 5657 Assn Std Single Material Response Stem            |
| <b>Material Document And Classification:</b>          | Ams5731 Assn Std Single Material Response Locking Ring     |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve          |
| <b>Surface Treatment:</b>                             | Cadmium Stem   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 1 Cl 2 Fed Spec Single Treatment Response Stem |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-4-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.