



Military-Fasteners.com

P/N CR3253-5-01

Description

diameter: 5/32", grip range: 0.025" - 0.062", universal head - oversized diameter - 5056 aluminum sleeve - 15-7 ph corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | CR3253501 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-150-5960 |



* See page 2 for technical characteristics

P/N CR3253-5-01 Specifications

| | |
|-----------------------------|---|
| Fastener Length: | 0.430 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Nominal |
| Shank Diameter: | 0.173 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.312 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.025 Inches Minimum And 0.062 Inches Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Corrosion Resisting Locking Ring |
| Material: | Steel Corrosion Resisting Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-5-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.