

**Description**

diameter: 5/32", grip range: 0.063" - 0.125", universal head, oversized diameter, 5056 aluminum sleeve, 15-7 ph corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR3253-5-2](#)

SKU / Model:	CR3253502
Minimum Qty (MOQ):	100
NSN:	5320-01-150-5961
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3253-5-02 Specifications

<b>Fastener Length:</b>	0.470 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Nominal
<b>Shank Diameter:</b>	0.173 Inches Nominal
<b>Head Major Diameter:</b>	0.312 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Corrosion Resisting Locking Ring
<b>Material:</b>	Steel Corrosion Resisting Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-5-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.