

Description

diameter: 5/32", grip range: 0.063" - 0.125", universal head, oversized diameter, 5056 aluminum sleeve, 15-7 ph corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3253-5-2](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | CR3253502                                   |
| Minimum Qty (MOQ):      | 100   |
| NSN:                    | 5320-01-150-5961                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N CR3253-5-02 Specifications

|                             |   |
|-----------------------------|---|
| <b>Fastener Length:</b>     | 0.470 Inches Nominal                          |
| <b>Head Style:</b>          | Universal                                     |
| <b>Head Height:</b>         | 0.067 Inches Nominal                          |
| <b>Shank Diameter:</b>      | 0.173 Inches Nominal                          |
| <b>Head Major Diameter:</b> | 0.312 Inches Nominal                          |
| <b>Expansion Device:</b>    | Serrated Stem-type W                          |
| <b>Grip Length:</b>         | 0.063 Inches Minimum And 0.125 Inches Maximum |
| <b>Material:</b>            | Aluminum Alloy 5056 Sleeve                    |
| <b>Material:</b>            | Steel Corrosion Resisting Locking Ring        |
| <b>Material:</b>            | Steel Corrosion Resisting Stem                |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-5-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.