

Description

diameter: 5/32", grip range: 0.313" - 0.375", universal head, oversized diameter, aluminum sleeve, corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3253-5-6](#)

| | |
|-------------------------|-----------------------|
| SKU / Model: | CR3253506 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-497-5239 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |

NO IMAGE
AVAILABLE

P/N CR3253-5-06 Specifications

| | |
|--|--|
| Fastener Length: | 0.466 Inches Minimum And 0.496 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.172 Inches Minimum And 0.176 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| End Item Identification: | F/a-18 Hornet; Cbr Ecp-904 |
| Grip Length: | 0.126 Inches Minimum And 0.187 Inches Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Iron Alloy 660 Locking Ring Or Steel Comp 304 Locking Ring |
| Material: | Steel Comp 632 Stem |
| Material Document And Classification: | Ams5657 Assn Std Single Material Response Stem |
| Material Document And Classification: | Ams5731 Assn Std 1st Material Response Locking Ring Or Ams5639 Assn Std 2nd Material Response Locking Ring |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Surface Treatment: | Cadmium Stem |
| Surface Treatment: | Passivate Locking Ring |
| Specification/standard Data: | 80205-nas9304 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-5-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.