

# P/N CR3253-5-07

Military-Fasteners.com

#### Description

diameter: 5/32", grip range: 0.376" - 0.437", universal head, oversized diameter, aluminum sleeve, corrosion resistant stem

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### Additional Information

SKU / Model:	CR3253507
Minimum Qty (MOQ):	100
NSN:	5320-01-150-5964
ECCN:	EAR99



## P/N CR3253-5-07 Specifications

Fastener Length:	0.790 Inches Nominal
Head Style:	Universal
Head Height:	0.067 Inches Nominal
Shank Diameter:	0.173 Inches Nominal
Head Major Diameter:	0.312 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Corrosion Resisting Locking Ring
Material:	Steel Corrosion Resisting Stem

### How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/CR3253-5-07</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.