

# P/N CR3253-5-10

### **Description**

Fastener Length: 31/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	CR3253510
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-150-5967
Schedule B:	7616.10.3000
FCCN:	94991



<sup>\*</sup> See page 2 for technical characteristics

## P/N CR3253-5-10 Specifications

Fastener Length:	0.980 Inches Nominal
Head Style:	Universal
Head Height:	0.067 Inches Nominal
Shank Diameter:	0.173 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.312 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.563 Inches Minimum And 0.625 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Corrosion Resisting Locking Ring
Material:	Steel Corrosion Resisting Stem

### **How to Order**

Order this cr max rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/CR3253-5-10">https://military-fasteners.com/rivets/blind+rivets/CR3253-5-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.