

**Description**

Fastener Length: 1/4", CR3253 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3253-5-03](#)

SKU / Model:	CR325353
Minimum Qty (MOQ):	100
NSN:	5320-01-287-7607
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N CR3253-5-3 Specifications

<b>Fastener Length:</b>	0.279 Inches Minimum And 0.309 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.172 Inches Minimum And 0.176 Inches Maximum
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Iron Alloy 660 Locking Ring Or Steel Comp 304 Locking Ring
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams5657 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Ams5731 Assn Std 1st Material Response Locking Ring Or Ams5639 Assn Std 2nd Material Response Locking Ring
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment:</b>	Passivate Locking Ring
<b>Specification/standard Data:</b>	80205-nas9304 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.