

Description

Fastener Length: 31/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3253-5-06](#)

SKU / Model:	CR325356
Minimum Qty (MOQ):	100
NSN:	5320-01-497-5239
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N CR3253-5-6 Specifications

Fastener Length:	0.466 Inches Minimum And 0.496 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	F/a-18 Hornet; Cbr Ecp-904
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Iron Alloy 660 Locking Ring Or Steel Comp 304 Locking Ring
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams5657 Assn Std Single Material Response Stem
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Locking Ring Or Ams5639 Assn Std 2nd Material Response Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment:	Passivate Locking Ring
Specification/standard Data:	80205-nas9304 Professional/industrial Association Standard

How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.