

Description

diameter: 3/16", grip range: 0.188" - 0.250", universal head, oversized diameter, 5056 aluminum sleeve, 15-7 ph corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3253-6-4](#)

SKU / Model:	CR3253604
Minimum Qty (MOQ):	100
NSN:	5320-01-529-4435
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3253-6-04 Specifications

Fastener Length:	0.390 Inches Nominal
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.200 Inches Minimum And 0.204 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
End Item Identification:	F/a-18 Hornet
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Iron Alloy 660 Grip Or Steel Comp 302 Grip Or Steel Comp 304 Grip Or Steel Comp 305 Grip Or Steel Comp 316 Grip Or Steel Comp 321 Grip Or Steel Comp 347 Grip Or Steel Comp 384 Grip Or Steel Comp 385 Grip
Material:	Iron Alloy 660 Locking Ring Or Steel Comp 304 Locking Ring
Material:	Steel Comp 632 Stem Or Iron Alloy 660 Stem
Material Document And Classification:	Ams-5657 Assn Std Single Material Response Stem Or Ams-5737 Assn Std Single Material Response Stem
Material Document And Classification:	Ams-5731 Assn Std Single Material Response Locking Ring Or Ams-5639 Assn Std Single Material Response Locking Ring
Material Document And Classification:	Ams-5737 Assn Std Single Material Response Grip Or Astm-a493 Assn Std Single Material Response Grip
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Stem Or Passivate Stem
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Passivate Grip
Surface Treatment:	Passivate Locking Ring
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Grip
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-416 Type I0.qq-p-416 Type I0cl 2 Fed Spec Single Treatment Response Stem Or Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-6-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.