

Description

diameter: 3/16", grip range: 0.313" - 0.375", universal head - oversized diameter - 5056 aluminum sleeve - 15-7 ph corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR3253606
Minimum Qty (MOQ):	100
NSN:	5320-01-150-5973
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N CR3253-6-06 Specifications

Fastener Length:	0.740 Inches Nominal
Head Style:	Universal
Head Height:	0.080 Inches Nominal
Shank Diameter:	0.201 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.375 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Corrosion Resisting Locking Ring
Material:	Steel Corrosion Resisting Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-6-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.