

P/N CR3253-6-10

Description

Fastener Length: 1"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | CR3253610 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-150-5977 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |



^{*} See page 2 for technical characteristics

P/N CR3253-6-10 Specifications

| Fastener Length: | 1.010 Inches Nominal |
|----------------------|---|
| Head Style: | Universal |
| Head Height: | 0.080 Inches Nominal |
| Shank Diameter: | 0.201 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.375 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.563 Inches Minimum And 0.625 Inches Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Corrosion Resisting Locking Ring |
| Material: | Steel Corrosion Resisting Stem |

How to Order

Order this cr max rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3253-6-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.