

**Description**

Fastener Length: 1-1/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR3253612
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-150-5979
Schedule B:	7616.10.3000
ECCN:	9A991



NO IMAGE  
AVAILABLE

## P/N CR3253-6-12 Specifications

<b>Fastener Length:</b>	1.140 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Nominal
<b>Shank Diameter:</b>	0.201 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.375 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.688 Inches Minimum And 0.750 Inches Maximum
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Corrosion Resisting Locking Ring
<b>Material:</b>	Steel Corrosion Resisting Stem

## How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-6-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.