

Description

Fastener Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | CR3253612 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-150-5979 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |



NO IMAGE
AVAILABLE

P/N CR3253-6-12 Specifications

| | |
|-----------------------------|---|
| Fastener Length: | 1.140 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Nominal |
| Shank Diameter: | 0.201 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.375 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.688 Inches Minimum And 0.750 Inches Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Corrosion Resisting Locking Ring |
| Material: | Steel Corrosion Resisting Stem |

How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-6-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.