

## Description

Blind Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[CR3253-6-03](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | CR325363                                  |
| Minimum Qty (MOQ):      | 100                                       |
| NSN:                    | 5320-01-529-4425                          |
| Schedule B:             | 7616.10.3000                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



\* See page 2 for technical characteristics

# P/N CR3253-6-3 Specifications

|  |   |
|--|---|
| Fastener Length:                               | 0.328 Inches Nominal  |
| Head Style:                                    | Universal   |
| Head Height:                                   | 0.080 Inches Minimum And 0.090 Inches Maximum   |
| Shank Diameter:                                | 0.200 Inches Minimum And 0.204 Inches Maximum   |
| Shank Style:                                   | Self-plugging Mechanically Locked Stem  |
| Head Major Diameter:                           | 0.356 Inches Minimum And 0.394 Inches Maximum   |
| End Item Identification:                       | F/a-18 Hornet   |
| Grip Length:                                   | 0.126 Inches Minimum And 0.187 Inches Maximum   |
| Material:                                      | Aluminum Alloy 5056 Sleeve  |
| Material:                                      | Iron Alloy 660 Grip Or Steel Comp 302 Grip Or Steel Comp 304 Grip Or Steel Comp 305 Grip Or Steel Comp 316 Grip Or Steel Comp 321 Grip Or Steel Comp 347 Grip Or Steel Comp 384 Grip Or Steel Comp 385 Grip |
| Material:                                      | Iron Alloy 660 Locking Ring Or Steel Comp 304 Locking Ring  |
| Material:                                      | Steel Comp 632 Stem Or Iron Alloy 660 Stem  |
| Material Document And Classification:          | Ams-5657 Assn Std Single Material Response Stem Or Ams-5737 Assn Std Single Material Response Stem  |
| Material Document And Classification:          | Ams-5731 Assn Std Single Material Response Locking Ring Or Ams-5639 Assn Std Single Material Response Locking Ring  |
| Material Document And Classification:          | Ams-5737 Assn Std Single Material Response Grip Or Astm-a493 Assn Std Single Material Response Grip   |
| Material Document And Classification:          | Qq-a-430 Fed Spec Single Material Response Sleeve   |
| Surface Treatment:                             | Cadmium Stem Or Passivate Stem  |
| Surface Treatment:                             | Chromate Sleeve   |
| Surface Treatment:                             | Passivate Grip  |
| Surface Treatment:                             | Passivate Locking Ring  |
| Surface Treatment Document And Classification: | Aa-p-416 Type I0.aa-p-416 Type I0cl 2 Fed Spec Single Treatment Response Stem Or Qq-p-35 Fed Spec Single Treatment Response Stem  |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Sleeve  |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Grip   |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Locking Ring   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3253-6-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.