

# P/N CR3253-6-8

### **Description**

Fastener Length: 7/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	CR325368
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-150-5975
Schedule B:	7616.10.3000
FCCN:	FAR99



<sup>\*</sup> See page 2 for technical characteristics

## P/N CR3253-6-8 Specifications

Fastener Length:	0.890 Inches Nominal
Head Style:	Universal
Head Height:	0.080 Inches Nominal
Shank Diameter:	0.201 Inches Nominal
Head Major Diameter:	0.375 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Corrosion Resisting Locking Ring
Material:	Steel Corrosion Resisting Stem

## **How to Order**

Order this cr max rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/CR3253-6-8">https://military-fasteners.com/rivets/blind+rivets/CR3253-6-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.