

**Description**


diameter: 1/8", grip range: 0.033" - 0.062", unisink head - locked spindle - oversized diameter - 5056 aluminum sleeve - 15-7 ph corrosion resistant stem, a286 corrosion resistant lock collar"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | CR3255401                                   |
| Minimum Qty (MOQ):      | 100   |
| NSN:                    | 5320-01-230-1807                            |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



## P/N CR3255-4-01 Specifications

|   |  |
|---|--|
| <b>Head Style:</b>                                    | Shovel   |
| <b>Head Height:</b>                                   | 0.022 Inches Minimum And 0.032 Inches Maximum              |
| <b>Shank Diameter:</b>                                | 0.139 Inches Minimum And 0.143 Inches Maximum              |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem                     |
| <b>Head Major Diameter:</b>                           | 0.210 Inches Minimum And 0.230 Inches Maximum              |
| <b>Countersink Height:</b>                            | 0.011 Inches Nominal                                       |
| <b>Expansion Device:</b>                              | Plain Stem-type T  |
| <b>Grip Length:</b>                                   | 0.033 Inches Minimum And 0.062 Inches Maximum              |
| <b>Special Features:</b>                              | 100 Deg Countersunk Head                                   |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve                                 |
| <b>Material:</b>                                      | Steel Comp 632 Stem  |
| <b>Material Document And Classification:</b>          | Ams5657 Assn Std Single Material Response Stem             |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve          |
| <b>Surface Treatment:</b>                             | Chromate Sleeve  |
| <b>Surface Treatment:</b>                             | Cadmium Stem   |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-5541 Mil Spec Single Treatment Response Sleeve       |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Stem |
| <b>Specification/standard Data:</b>                   | 80205-nas9306 Professional/Industrial Association Standard |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3255-4-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.