

Description

Cr Max Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | CR325542 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-01-229-8190 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3255-4-2 Specifications

| | |
|---|--|
| Head Style: | Shovel |
| Head Height: | 0.022 Inches Minimum And 0.032 Inches Maximum |
| Shank Diameter: | 0.139 Inches Minimum And 0.143 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.210 Inches Minimum And 0.230 Inches Maximum |
| Countersink Height: | 0.011 Inches Nominal |
| Expansion Device: | Plain Stem-type T |
| Grip Length: | 0.063 Inches Minimum And 0.125 Inches Maximum |
| Special Features: | 100 Deg Countersunk Head |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Comp 632 Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Material Document And Classification: | Ams5657 Assn Std Single Material Response Stem |
| Surface Treatment: | Chromate Sleeve |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Stem |
| Specification/standard Data: | 80205-nas9306 Professional/Industrial Association Standard |

How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3255-4-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.