

Description

Cr Max Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR325563
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-231-3890
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3255-6-3 Specifications

Head Style:	Shovel
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.200 Inches Minimum And 0.204 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.343 Inches Minimum And 0.363 Inches Maximum
Countersink Height:	0.023 Inches Nominal
Expansion Device:	Plain Stem-type T
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Special Features:	100 Deg Countersunk Head
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 632 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Ams5657 Assn Std Single Material Response Stem
Surface Treatment:	Chromate Sleeve
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas9306 Professional/Industrial Association Standard

How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3255-6-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.