

**Description**

Cr Max Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR325566
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-229-9625
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3255-6-6 Specifications

<b>Head Style:</b>	Shovel
<b>Head Height:</b>	0.040 Inches Minimum And 0.050 Inches Maximum
<b>Shank Diameter:</b>	0.200 Inches Minimum And 0.204 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.343 Inches Minimum And 0.363 Inches Maximum
<b>Countersink Height:</b>	0.023 Inches Nominal
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Special Features:</b>	100 Deg Countersunk Head
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Material Document And Classification:</b>	Ams5657 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Chromate Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Stem
<b>Specification/standard Data:</b>	80205-nas9306 Professional/industrial Association Standard

## How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3255-6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.