

Description

diameter: 1/8", grip range: 0.438" - 0.500", flush head, monel sleeve, corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3522-4-8](#)

| | |
|--------------------|------------------|
| SKU / Model: | CR3522408 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-483-0501 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N CR3522-4-08 Specifications

| | |
|--|--|
| Fastener Length: | 0.760 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.126 Inches Nominal |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.225 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| Grip Length: | 0.500 Inches Nominal |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Nickel Alloy Sleeve |
| Material: | Steel Corrosion Resisting Locking Ring |
| Material: | Steel Corrosion Resisting Stem |
| Material Document And Classification: | Ams5657 Assn Std 3rd Material Response Stem |
| Material Document And Classification: | Ams5731 Assn Std 1st Material Response Locking Ring |
| Material Document And Classification: | Qq-n-281 Fed Spec 2nd Material Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3522-4-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.