

Description

diameter: 5/32", grip range: 0.126" - 0.187", flush head, monel sleeve, corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3522-5-3](#)

SKU / Model:	CR3522503
Minimum Qty (MOQ):	100
NSN:	5320-01-150-2743
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR3522-5-03 Specifications

Fastener Length:	0.530 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.157 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.286 Inches Nominal
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Nickel Alloy Sleeve
Material:	Steel Corrosion Resisting Locking Ring
Material:	Steel Corrosion Resisting Stem
Material Document And Classification:	Ams5657 Assn Std 3rd Material Response Stem
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Locking Ring
Material Document And Classification:	Qq-n-281 Fed Spec 2nd Material Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3522-5-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.